Page 1/4

1 Identification of the substance and manufacturer Trade name: DEGALVANIZER Product code: FG00200343 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Seymour of Sycamore Seymour of Sycamore Manufacturer/Supplier: 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com www.seymourpaint.com 1-800-255-3924 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flam. Aerosol 1 H222 Extremely flammable aerosol. Press. Gas H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. Eye Irrit. 2A STOT SE 3 H336 May cause drowsiness or dizziness. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS Hazard pictograms GHS02 GHS04 GHS07 GHS08 Signal word Danger Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ing	redients	
Chemical characterization: Mixture Chemical Description:	s This product is a mixture of the substances listed below with nonhazardous additior	S.
Dangerous components:		
8042-47-5 White mineral oil, petroleu	m	27.09%
8012-95-1 Petroleum hydrocarbon		22.37%
67-64-1 Acetone		14.74%
8008-20-6 Kerosine (petroleum)		11.44%
74-98-6 propane		6.3%
106-97-8 n-butane		3.7%
2807-30-9 Glycol Ether EP		3.23%
After skin contact: After eye contact: After swallowing: Most important symptoms and effects: Indication of any immediate medica attention needed:	Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse mouth with water. Do not induce vomiting. Dizziness No further relevant information available.	
5 Fire-fighting measures Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.	(Contd. on page 2

Printing date 09/24/2019

Safety Data Sheet

Revised On 09/24/2019

Page 2/4

	(Contd. of pa
Special hazards:	Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.
Accidental release measures Personal precautions, protective	
equipment and emergency	
procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Absorb liquid components with liquid-binding material.
containment and cleaning up.	
Handling and storage	
Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditi Store locked up.
Exposure controls/personal p	rotection
<u> </u>	at require monitoring at the workplace:
8012-95-1 Petroleum hydrocarbo	
PEL (USA) Long-term value: 5 mg	
REL (USA) Short-term value: 10 m	g/m³
Long-term value: 5 mg	/m³
oil mist TLV (USA) L	
67-64-1 Acetone	
PEL (USA) Long-term value: 2400	ma/m ³ , 1000 ppm
REL (USA) Long-term value: 590 r	
TLV (USA) Short-term value: 1187	
Long-term value: 594 r	ng/m³, 250 ppm
BEI	
8008-20-6 Kerosine (petroleum)	/ 3
REL (USA) Long-term value: 100 r Kerosine only	ng/m²
TLV (USA) Long-term value: 200 r	ng/m³
as total hydrocarbon va	apor; Skin; P
74-98-6 propane	
PEL (USA) Long-term value: 1800	
REL (USA) Long-term value: 1800	
TLV (USA) refer to Appendix F inT	LVs&BEIs book; D, EX
106-97-8 n-butane	
REL (USA) Long-term value: 1900	
TLV (USA) Short-term value: 2370 (EX)	mg/m, rood ppm
Ingredients with biological limit	/alues:
67-64-1 Acetone	
BEI (USA) 50 mg/L	
Medium: urine	
Time: end of shift Parameter: Acetone (no	nspecific)
Hygienic protection:	Wash hands after use.
	Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open area cases where short and/or long term overexposure exists, a charcoal filter respirator should be w
	If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Nitrile gloves.
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles
	ואראי שבמובע איטאוניש
Physical and chemical proper	
Appearance:	Aerosol.
Odor: Odor threshold:	Aromatic Not determined.
	Not determined.
pH-value: Melting point/Melting range	Undetermined.

Safety Data Sheet

Printing date 09/24/2019

Revised On 09/24/2019

Trade name: DEGALVANIZER		
Boiling point:	-44 °C (-47.2 °F) (Contd. of page 2)	
Flash point:	-19 °C (-2.2 °F)	
Flammability (solid, gas):	Extremely flammable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. Not determined. Not determined.	
Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. : Not determined.	
Solubility: Viscosity: VOC content (less exempt solvents):	Not determined. Not determined. : 13.3 %	
10 Stability and reactivity		
Reactivity: Conditions to avoid: Chemical stability:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated.	
Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.	
11 Toxicological information		
LD/LC50 values that are relevant for	classification:	
106-97-8 n-butane		
Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effects:	No data available	
Skin effects: Eye effects: Sensitization:	No irritant effect. No irritating effect. No sensitizing effects known.	
12 Ecological information Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.	
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.	
13 Disposal considerations		
Dispose of in accordance with local, st	ate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be cut empty containers with electric or gas torches. Completely empty cans should be recycled.	
14 Transport information		
UN-Number	UN1950	
DOT DOT	N/A Consumer Commodity ORM-D	
	Aerosols, flammable	
ADR	1950 Aerosols	
Transport hazard class(es): Class	2.1	
Marine pollutant:	No	
Special precautions for user: EMS Number:	Warning: Gases F-D,S-U	
Packaging Group: UN "Model Regulation":	UN1950, Aerosols, 2.1	
	(Contd. on page 4)	

Revised On 09/24/2019

Trade name: DEGALVANIZER

(Contd. of page 3)

15 Pagulatony information				
15 Regulatory information				
SARA Section 355 (extremely hazardous substances):				
None of the ingredients in this product are listed.				
SARA Section 313 (Specific tox	ic chemical listings):			
None of the ingredients is listed.				
Toxic Substances Control Act (TSCA): Canadian Domestic Substances	All hazardous ingredients are found on the inventory list of substances.			
(DSL): Consumer Product Safety	All ingredients are listed or exempted.			
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.			
California Proposition 65 chemi	icals known to cause cancer:			
None of the ingredients in this pro-	duct are listed.			
Prop 65 chemicals known to car	use birth defects or reproductive harm:			
None of the ingredients is listed.				
EPA:				
67-64-1 Acetone	1			
16 Other information				
Contact:	Regulatory Affairs			